

NUVAIR STANDARD GAS



This compressor is powered by a 4-stroke gas engine. The frame has been constructed to allow a three-phase electric motor to be fitted if required. This is a light weight unit with lifting handles for easy transportation.

	Model 7	Model 9
Filling Time*	9 Minutes	7.4 Minutes
Cubic Feet/Minute	7.6 FAD 8.9 SCFM	9.4 FAD 10.8 SCFM
Liters/Minute	215	265
Engine	Honda (Model#8021)	Honda (Model#8024)
Engine Power	6.5 hp (4.9 kW)	9 hp (6.6 kW)
Max. Op. Pressure	5000 PSI (345 bar)	5000 PSI (345 bar)
RPM	1350	1550
Number of Stages	3	3
Number of Fill Hoses	2	2
Condensate Drain	Manual	Manual
Sound Level @ 3 Meters	92 dB	92 dB
Dimensions (HxWxD)	25" x 45" x 19"	25" x 45" x 19"
	(64 x 113 x 47 cm)	(64 x 113 x 47 cm)
Weight	232 lbs (105 kg)	253 lbs (115 kg)
Lubrication	Splash lubrication, capacity 1.6 qt.	
Air Quality	DIN 3188/CGA Grade E	

*Single 80 cu ft cylinder from 500 to 3000 PSI

Nuvair™
 2949 West Fifth Street Oxnard, CA 93030
 Office: 1-805-815-4044 Fax: 1-805-815-4196
www.nuvair.com

Terms and Conditions:
 50% Deposit at time of order. Balance due prior to shipping.
 FOB Oxnard, CA USA. Specifications and price subject to
 change without notice.