Traveler II™

This complete turn key Nitrox System is built for the diver that wants to fill tanks while away from Dive Shops. With this system you can easily fill Nitrox or air while on remote locations (home, vacations or offshore).

Featured with Optional Wheels

Features

- Four Stage 4.2 SCFM* High Pressure Compressor
- Fill O_2% 21-40%
- Nuvair 6 CFM Membrane System
- Pro O_2 Analyzer for Fill O_2%
- Pick O_2 Analyzer for Permeate Inline O_2%
- 110 or 220 Volt Thermostatically Controlled Heater
- LP > LP Regulator for O_2% Adjustment
- LP Supply Pressure and Regulated Pressure Gauges
- Norgren Series 74 LP Filtration, Auto Drains/Dual Pressure Gauges, Coalescing 1.0 Micron, Polishing 0.01 Micron, Oil Vapor Removal 0.003 PPM
- 11 hp Honda Electric Start, 13 amp Charging Circuit
- Tach/Hour Meter
- 600 Watt Inverter
- 12 Volt Battery

Options

- Automatic Condensate Drains
- High Temperature Shut Down
- Automatic Fill Pressure Shut Down
- Preset Maximum Fill Blocks 3000 psi and 4500 psi
- Solar Charger
- Electric Motor, 220 Volt Single or Three Phase, 50 or 60 Hz

Nitrox Traveler II Model		Gas (Part#7052G)	Electric (Part#7052E)
Physical Specifications	**Height** **Width** **Depth** **Weight**	48 in (122 cm) 51 in (130 cm) 20 in (51 cm) 385 lbs (175 kg)	48 in (122 cm) 51 in (130 cm) 20 in (51 cm) 410 lbs (186 kg)
LP Compressor	**Capacity @ 175 psi**	12 CFM (340 L/min.)	12 CFM (340 L/min.)
Volume Tank	**Capacity**	15 gal (57L)	15 gal (57L)
Membrane Input	**Operating Pressure** **Supply Air Volume** **Optimum Temperature**	90-165 psi (6-11 bar) 4-12 CFM (113-340 L/min.) 110 +/- 5° F (43 +/-3° C)	90-165 psi (6-11 bar) 4-12 CFM (113-340 L/min.) 110 +/- 5° F (43 +/-3° C)
HP Nitrox Compressor	**Output** **Charging Rate** **Fill Time (80 Cu.. Ft.)** **Horsepower - Electric** **Horsepower - Gas**	3.5 CFM, F.A.D. (100 L/min.) 4.2 SCFM* 22 minutes* 7.5 hp (5.5 kW) 11 hp (8.2 kW)	3.5 CFM, F.A.D. (100 L/min.) 4.2 SCFM* 22 minutes* 7.5 hp (5.5 kW) 11 hp (8.2 kW)

*Single 80 Cu.. Ft. cylinder from 500 - 3000 psi

info@nuvair.com **www.nuvair.com**
Phone: 1-805-815-4044 Fax: 1-805-815-4196
2949 West Fifth Street Oxnard, CA 93030 USA

REV: 04/01/2010