



Coltri/Nuvair 26 Enclosed Silenced

High volume facilities where sound may be an issue should look at our Enclosed Silent 26.4 SCFM* charging rate compressor, rated for continuous duty at up to 6000psi. Unsurpassed in quality, reliability and price. The Enclosed Silenced package is designed for high use in work areas where noise can not be tolerated.

Features

- Substantial reductions in purchase, maintenance and operation costs as compared to our competition.
- Operation Panel with start/stop, "dial a pressure" automatic shut down, condensate test button, high temperature display, automatic shut down for high temperature & low oil, phase control (proper rotation) recognition, wrong voltage recognition, hour meter, stage & oil pressure gauges
- Automatic Condensate Drains and pressure free start/stop
- Low pressure oil pump, filter & oil level sight gauge
- Large Stainless Steel Interstage cooling tubes with large condensate separators
- Dual Filter Filtration 60,000 Cu.. Ft.
- 20hp or 15hp Electric 3 phase 60 or 50Hz



Options

- CO/Moisture Monitor
- CO Analyzer
- Additional Filtration

Model	MCH30 / 21	MCH36 / 26
Filling Time*	Approx. 4 Minutes	Approx. 3.3 Minutes
Cubic Feet/Minute	17.5 FAD 21 SCFM*	22 FAD 26.4 SCFM*
Liters/Minute	500 FAD	623 FAD
Engine	Three Phase	Three Phase
230 V/E3/60 Hz	31 Amp 15 hp (11 kw) (Part #8043.2)	35.5 Amp 20 hp (15 kw) (Part #8045.2)
400V/E3/50 Hz	18 Amp 15 hp (11 kw) (Part #8043.6)	20 Amp 20 hp (15 kw) (Part #8045.6)
460V/E3/60 Hz	16 Amp 15 hp (11 kw) (Part #8043.3)	22 Amp 20 hp (15 kw) (Part #8045.3)
Max Operating Pressure	6000 PSI (414 Bar)	6000 PSI (414 Bar)
RPM	1100	1300
Number of Stages	4	4
Number of Fill Hoses	4	4
Condensate Drain	Automatic	Automatic
Fill Pressure Stop	Automatic	Automatic
Sound Level @ 3 Meters	68 dB	70 dB
Dimensions: (H x W x D)	65.5 in x 37 in x 52 in (169 x 94 x 132 cm)	
Weight	925 lbs (420 kg)	
Lubrication	Pressure Lubrication, capacity 4.5 qts.	
Air Quality	DIN 3188/CGA Grade E	

*Single 80 Cu. Ft. cylinder from 500 to 3000 PSI

info@nuvair.com www.nuvair.com
 Phone: 1-805-815-4044 Fax: 1-805-815-4196
 2949 West Fifth Street Oxnard, CA 93030 USA