



Coltri/Nuvair Compact & EVO (Models 7 and 9)

The Compact Series includes a semi-sound proofed filling station. The compressor switches off automatically when the pressure level set by the operator is reached. Condensate is discharged automatically. External access simplifies oil level monitoring and changes. The Compact is also offered as an EVO model with Interstage Pressure Gauges, High Temp, and Low Oil Shutdown included.

Features

- Motor Starter
- Automatic Condensate Drains
- Dial-A-Pressure Switch
- Hour Meter
- Semi-Sound Proofed Cabinet
- External Oil Sight Gauge
- Grade E Filtration
- Automatic Stop

Options (included on EVO models)

- Interstage Pressure Gauges
- High Temp Shut Down
- Low Oil Shut Down
- CO Monitor



EVO Cabinet

Model	MCH13 / 7	MCH16 / 9
Filling Time*	Approx. 9 Minutes	Approx. 7.4 Minutes
Cubic Feet/Minute	7.6 FAD 8.9 SCFM*	9.4 FAD 10.8 SCFM*
Liters/Minute	215 FAD	265 FAD
Engine Options	Single or Three Phase	Single or Three Phase
230 V/E1/50-60 Hz	25 Amp	34 Amp (Part# 8033.1)**
230 V/E3/50-60 Hz	14 Amp	20 Amp (Part# 8032.2)**
440 V/E3/50-60 Hz	7 Amp	10 Amp (Part# 8032.3)**
Engine Power	5.5 hp (4 kW)	7.5 hp (5.5 kw)
Max Operating Pressure	5000 PSI (345 Bar)	5000 PSI (345 Bar)
RPM	1350	1550
Number of Stages	3	3
Number of Fill Hoses	2	2
Condensate Drain	Automatic	Automatic
Fill Pressure Stop	Automatic	Automatic
Sound Level @ 3 Meters	79 dB	81 dB
Dimensions***: (H x W x D)	33 in x 35 in x 24 in (84 x 89 x 60 cm)	33 in x 35 in x 24 in (84 x 89 x 60 cm)
Weight	310-400 lbs (141-181 kg)	332-430 lbs (151-195 kg)
Lubrication	Splash Lubrication, capacity 1.6 qts.	
Air Quality	DIN 3188/CGA Grade E	

***Single phase enclosure 33 in x 42 in x 28 in (84 x 105 x 70 cm)

*Single 80 Cu. Ft. cylinder from 500 to 3000 PSI

** Part number reflects 60Hz Model. Inquire about 50 Hz Model

info@nuvair.com

www.nuvair.com

Phone: 1-805-815-4044 Fax: 1-805-815-4196

2949 West Fifth Street Oxnard, CA 93030 USA