



Coltri/Nuvair Mini Silent

The Mini Silent Series uses a very compact, sound proofed container. Completely automatic operation ensures that the compressor switches off when the maximum pressure set on the dial a pressure switch is reached. The condensate periodically drains through automatic pneumatic valves into a collection tank. Due to it's small footprint this compressor is great for use in boats and shops.

Features:

- Motor Starter
- Automatic Condensate Drains
- Dial-A-Pressure Switch
- Hour Meter
- Sound Proof Cabinet
- External Oil Sight Gauge
- Grade E Filtration
- Automatic Stop

Options:

- Interstage Pressure Gauges
- High Temp Shut Down
- Low Oil Shut Down
- CO/Moisture Monitor
- Additional Filtration



Model	MCH13 / 7	MCH16 / 9
Filling Time*	Approx. 9 Minutes	Approx. 7.4 Minutes
Cubic Feet/Minute	7.6 FAD 8.9 SCFM*	9.4 FAD 10.8 SCFM*
Liters/Minute	215 FAD	265 FAD
Engine Options	Single or Three Phase	Three Phase
230 V/E1/50-60 Hz	25 Amp	N/A
230 V/E3/50-60 Hz	14 Amp	20 Amp (Part#8034.2)**
440 V/E3/50-60 Hz	7 Amp	10 Amp (Part#8034.3)**
Engine Power	5.5 hp (4 kW)	7.5 hp (5.5 kw)
Max Operating Pressure	5000 PSI (345 Bar)	5000 PSI (345 Bar)
RPM	1350	1550
Number of Stages	3	3
Number of Fill Hoses	2	2
Condensate Drain	Automatic	Automatic
Fill Pressure Stop	Automatic	Automatic
Sound Level @ 3 Meters	72 dB	75 dB
Dimensions: (H x W x D)	42 in x 28 in x 25 in (105 x 70 x 62 cm)	42 in x 28 in x 25 in (105 x 70 x 62 cm)
Weight	390 lbs (177 kg)	410 lbs (187 kg)
Lubrication	Splash Lubrication, capacity 1.6 qts.	
Air Quality	DIN 3188/CGA Grade E	

*Single 80 Cu. Ft. cylinder from 500 to 3000 PSI

** Part number reflects 60Hz Model. Inquire about 50 Hz Model

info@nuvair.com www.nuvair.com
 Phone: 1-805-815-4044 Fax: 1-805-815-4196
 2949 West Fifth Street Oxnard, CA 93030 USA