

NUVAIR™ LP-LP 12

- Complete state-of-the-art LP/LP Nitrox generating system.
- Compressors can be used independently to provide low pressure air or together, to provide Nitrox.
- Latest membrane technology. *Now up to 20% more efficient.*
- Produces a constant flow of Nitrox from 22% to 40% O₂ at 12 scfm at 150 psi

Specifications

- LP Air Filtration: Norgren Series 74
 - Auto Drain/Dp Gauges
 - Coalescing 1.0 Micron
 - Fine Polishing 0.01 Micron
 - Oil Vapor Removal 0.003 ppm
 - LP Pressure Regulator
- Supplying Grade D Air
- ABAC LP - Rated to 12 cfm @ 150 psi
- Champion R15 - Rated to 23 cfm @ 175 psi
- LP Dual Control Head Un-loaders
- (2) Air After Coolers
- Air Tank - (1) Steel 30 Gallon
- Fuel - 6.5 Gallons
- Weight 624 lbs.
- H 57" x W 53" x D 23"
- Honda 20 Hp Electric Start Engine
- 12 Volt Battery with Box
- 20 Amp Charging System
- 600 Watt Inverter
- Hour Meter/Tachometer

Nitrox Membrane System

- (2) Pro O₂ Analyzers (Permeate & Diver Supply)
- Membrane



Nuvair™

2949 West Fifth Street Oxnard, CA 93030
Office: 1-805-815-4044 Fax: 1-805-815-4196
www.nuvair.com



- Auto Thermostatic Control 110/220 Volt Heater
- Air Intake Filter & Static Mixing Tube
- Food-Grade Compressor Lubricant for Nitrox Breathing Applications (Nuvair 455)
- Mix Accurate to Within 1/10%

Features

- Rigid 2" Sq. Aluminum Frame & Belt Guard
- 1/4" Stainless Steel Compressor Mounting Plate
- Vibration Mounts Below Compressor Plate & Frame
- Produce LP Air at 23 cfm 175psi or Nitrox at 12 cfm 22-40% O₂ 150 psi

Options

- 27 Hp Duetz Diesel or Electric 15 Hp 3 Phase Motor
- 60 Gallon Volume Tank
- Pressure Lubricated Compressor Rated to 250 psi
- Low Oil Shutdown
- High Temperature Shutdown
- Low/High O₂% Shut Down or Alarm
- Additional Diver LP Filtration

Terms and Conditions:

50% Deposit at time of order. Balance due prior to shipping. FOB Oxnard, CA USA. Specifications and price subject to change without notice.