



## Coltri/Nuvair 250

The Tech 250 has the features of the Mini Tech plus a panel for gauges, fill whips or anything else that you would like mounted on it. There is also extra room for upgraded filtration.

### Features

- 5000 PSI Max Pressure
- Grade E Filtration
- 2 Fill Whips
- Electric or Honda Gas Motor
- Stainless Steel Intercoolers
- 4 Lifting Handles
- All Important Parts are Protected Inside Frame
- Superior Vibration Isolation
- Gauge Panel
- Removable Air Intake Snorkel

### Options

- Motor Starter/Electric Start
- Automatic Condensate Drains
- Pressure Switch
- Hour Meter
- High Temp Shut Down
- Low Oil Shut Down
- Interstage Pressure Gauges
- Stainless Frame
- Visual CO/Moisture Indicator
- Upgrade Filtration



Model	MCH16 / 250
Filling Time*	Approx. 7.4 Minutes
Cubic Feet/Minute	9.4 FAD 10.8 SCFM*
Liters/Minute	265 FAD
Engine Options	Single or Three Phase
230 V/E1/50-60 Hz	34 Amp 7.5 hp (5.5 kw) (Part# 8030.1)
230 V/E3/50-60 Hz	20 Amp 7.5 hp (5.5 kw) (Part# 8031.2)
440V/E3/50/60 Hz	10 Amp 7.5 hp (5.5 kw) (Part# 8031.3)
Honda Gas (Electric Start)	9 hp (6.6 kW) (Part# 8027-EL)
Yanmar Diesel (Electric Start)	10 hp (7.5kW) (Part# 8028-DY-EL)
Max Operating Pressure	5000 PSI (345 Bar)
RPM	1550
Number of Stages	3
Number of Fill Hoses	2
Condensate Drain	Manual
Sound Level @ 3 Meters	80-96 dB
Dimensions: (H x W x D)	31 in x 44 in x 23 in (79 x 112 x 58 cm)
Weight	320-421 lbs (145-191 kg)
Lubrication	Splash Lubrication, capacity 1.6 qts.
Air Quality	DIN 3188/CGA Grade E

\* Single 80 Cu.. Ft. cylinder from 500 to 3000 PSI

\*\* Part number reflects 60Hz Model. Inquire about 50 Hz Model

info@nuvair.com

www.nuvair.com

Phone: 1-805-815-4044 Fax: 1-805-486-0900

1600 Beacon Place, Oxnard, CA 93033 USA