

NUVAIR STANDARD DIESEL

YANMAR



HONDA



The Diesel engine driven compressor is for operators that do not have electric power available and prefer the safety benefits of diesel fuel. They are very smooth running packages that are extremely economical to operate. The frame is protected with powdered epoxy paint. Portable filling station that is powered by a single-cylinder diesel engine. Vibration is kept to a minimum by the use of rubber insulators on the base of the all-purpose frame. Available in pull start and electric start.

	Yanmar	Honda
Filling Time*	7.4 Minutes	7.4 Minutes
Cubic Feet/Minute	9.4 FAD 10.8 SCFM	9.4 FAD 10.8 SCFM
Liters/Minute	265	265
Engine	Yanmar (Model#8025)	Honda (Model#8026)
Engine Power	10 hp (7.5 kW)	9 hp (6.6 kW)
Max. Op. Pressure	5000 PSI (345 bar)	5000 PSI (345 bar)
RPM	1550	1550
Number of Stages	3	3
Number of Fill Hoses	2	2
Condensate Drain	Manual	Manual
Sound Level @ 3 Meters	80 dB	96 dB
Dimensions (HxWxD)	25" x 45" x 19" (64 x 113 x 48 cm)	25" x 45" x 19" (65 x 111 x 48 cm)
Weight	299 lbs (136 kg)	326 lbs (148 kg)
Lubrication	Splash lubrication, capacity 1.6 qt.	
Air Quality	DIN 3188/CGA Grade E	

*Single 80 cu ft cylinder from 500 to 3000 PSI

Nuvair™
 2949 West Fifth Street Oxnard, CA 93030
 Office: 1-805-815-4044 Fax: 1-805-815-4196
 www.nuvair.com

Terms and Conditions:
 50% Deposit at time of order. Balance due prior to shipping.
 FOB Oxnard, CA USA. Specifications and price subject to
 change without notice.