



Nardi Diving Hookah 5G Petrol INSTRUCTIONS BOOKLET 7 Litre Tank Capacity (with 17m Hose & Regulator)



The 5G Petrol Hookah in NARDI COMPRESSORI's oilless range suits medium duty applications supplying multiple divers while remaining remarkably compact and lightweight. The rugged design incorporates a **7 litre air tank**.

The CE mark indicates that the compressor complies with CEE Directives 89/392, 89/336, 87/404, EN 292/2, EN 294, EN 60204-1

Manufactured in Italy, the NARDI diving Hookah range utilise their renowned oilless piston compressor pumping units, distributed around the world with a well-deserved reputation for quality, reliability, and quiet operation.

The NARDI HOOKAH compressor provides vastly **superior performance, pressure, and reliability**. The true oilless design of the compressor unit provides **guaranteed air quality** and **superior safety**.

Power Source: Petrol - Regular Unleaded (1.5 Litre Tank)

Running Time: Approx. 2 Hours from Full Fuel Tank

Engine: 3hp

Compressor: 2 Cylinder / Oilless

Air Intake: 5G 60 = 270 lpm (9.5 cfm) & 5G 70 = 380 lpm (13.4 cfm)

Air Filtration: Replaceable Cartridge (NARDI original)

Air Quality: Compliant With AS1715:2009 (Air Quality Requirements)

Pressure - Tank: 10 Bar (142 psi)

Pressure - Outlet: Adjustable - 0 to 10 Bar (0 to 142 psi)

Tank: 7 Litre

Max. Number Of Divers: 2

Max. Recommended Depth: 20 metres

Unit Dimensions: 420mm(L) X 450mm(W) X 450mm(H)

Packaged Dimensions: 500mm(L) x 480mm(W) x 480mm(H)

Unit Weight: 25.5 kg

Packaged Weight: 26.5 kg

Noise: 85 dB

Warranty: 12 Months

The Nardi range of Surface Supply Diving Hookahs are ideal for both recreational activities and commercial work and are mostly appreciated in :

- Recreational Diving • Boat Maintenance • Pier and Marina Maintenance
- Swimming Pool Maintenance • Diver Training • Marine Research

The included Hose/Regulator is 17 metres long with quick-connect fittings. Utilising the 'Additional Diver Kit' which incorporates a T-Coupling and an additional Hose/Regulator (sold separately) the unit can supply a second diver. Hose Extensions (17m) can also be purchased separately.

The output pressure is manually adjustable. The compressor works without oil and the quality of air delivered conforms to all relevant legislation regarding breathable air.

Safety Note: When using a Surface Supplied Diving Apparatus (SSBA) you are still breathing compressed air. This can be hazardous if you have not been properly trained.



ADDITIONAL DIVER KIT

The genuine NARDI Additional Diver Kit includes a T-Coupling along with a Hose & Regulator to fit directly to the breathing air outlet on your diving hookah. This is the same Hose and Regulator that comes as standard equipment with your diving hookah and will allow a second diver to operate from the same unit.

Hose Length: 17m

Hose ID: 8mm

Hose OD: 15mm



EXTENSION HOSE

The genuine Nardi Extension Hose fits directly to the breathing air outlet on your diving hookah and extends the length of a standard NARDI Hose & Regulator to 34m.

Hose Length: 17m

Hose ID: 8mm

Hose OD: 15mm



FILTER CARTRIDGE

Genuine NARDI Replacement Filter Cartridge for breathing air. This item suits petrol model diving hookahs. Cartridges go through a decontamination process and are then sealed, and vacuum packed to ensure integrity during storage. Nardi Part Number: AC036-102

CORRECT USE OF THE NARDI HOOKAH COMPRESSOR WITH PETROL ENGINE

NARDI COMPRESSORI kindly asks you to read the following instructions and to follow them carefully before you start using the machine in order to avail yourself of its potentialities without endangering your safety or damaging the compressor.

Safety Precautions

Strictly observe the following safety measures:

Move the compressor by suitable means to avoid an excessive effort to your upper and lower limbs.

In case of prolonged use, protectors such as earphones are recommended.

Do not move the compressor while in operation, avoid causing health risks due to exposure to vibrations of limbs (hand-arm).

Do not tamper with the compressor, if you need to perform maintenance or any repair contact your supplier immediately.

Do not use in closed environments with a limited circulation of air.

Do not use the compressor near flames or heat sources, and keep away from kids and animals.

Please avoid a prolonged exposure of the machine under direct sun rays; the suggested working temperature should be between +5 and +50 ° C.

Keep away from children and animals at all times.

Do not use the compressor in dusty environments.

Do not tamper with its safety devices and regulation.

Starting the machine:

Make sure no damages due to carelessness or negligence occurred during transportation, before you start the machine. If this should be the case, notify the dealer or transportation company immediately. After having checked the compressor observe the following instructions:

The compressor is equipped with an air flow adjuster which enables the operator to control the working pressure. Said pressure can be visualised on the manometer.

Before starting the petrol engine make sure the air hose is not under pressure and the air outlet fitting is open.

- Fill the petrol tank with the suitable petrol;
- Open the petrol tap so that the fuel enters the engine;
- Turn ON the on-off switch
- Turn the lever next to the motor filter
- Unscrew the black lever positioned next to the breaker valve so that the compressor can start without strain;
- Pull the engine start and wait for some time
- Close air in the motor
- Screw black lever (next to the breaker valve)
- The compressor will now reach its set working pressure.

Turning OFF the machine:

- Check manometer to ensure that compressor is at its max pressure before turning OFF the compressor.
- Release the air from the tank by screwing the black lever (next to breaker valve)
- Turn the ON-OFF switch to OFF.

DO NOT STOP the engine while the compressor air tank is under pressure.

Maintenance:

Unscrew filter and clean it periodically by an air jet moving from the center to the outside.

Because of the compressor and rapid expansion of the air inside the tank, the humidity in the air condensates. It is therefore necessary to periodically discharge the condensate from the tank by unscrewing the drain plug and slightly tilting the tank.

Replace filter cartridge as soon as you feel that the air is smelly, approximately every 20/30hrs.

Warranty. The compressor is guaranteed for a period of 12 months against any manufacturing failure. It is important to keep to original purchasing receipt as a proof for the validity of the warranty. The date on the original data sticker on the compressor is valid for the warranty time calculation. DO NOT REMOVE DATA STICKER – THIS WOULD NULLIFY WARRANTY RIGHTS.

Use the compressor as indicated in this booklet and only for the purpose it has been designed for by the manufacturer. The warranty covers only the replacement of those parts which are faulty because of any assembly or manufacturing defects. All transportation or operation fees are charged to clients.



Recycling:

The compressor must be scrapped according to disposal norms in the country where it will be disposed of.

NARDI COMPRESSORI thanks you for respecting the environment.



Nardi Compressori Srl
Via Marco Polo, 2 36075
Montebelluna Maggiore (VICENZA) ITALY
Tel. +39.0444.159111 - 497514 - 694885
Fax. +39.0444.159122
Mail. info@nardicompressori.com

